

Questionnaire



Fax	+49 2392 5006-180	Date	
E-Mail	sales@brinkmannpumps.de		

Contact details	
Company	
Address	
Contact partner	
Telephone	
E-Mail	

Pump	
Application	
Requirement per year (each)	

Pumping data	
Flow rate (l/min.)	
Pressure (bar)	
Delivery head (m)	

Dimensions	
Immersion depth	

Medium to be pumped	
Type	
Temperature (°C)	
Viscosity at pumping temperature (mm ² /s, cSt)	
Density (kg/l)	
Percentage of solids (g/l)	
Size of solids (mm/mm)	
pH value	
Percentage of air in medium	

Pump materials	
Pump body	
Cover	
Impeller	
Shaft	
Seals	

Drive			
laid out for line power	<input type="checkbox"/> 3 x 400 V, 50 Hz	<input type="checkbox"/> 3 x 440 V, 60 Hz	<input type="checkbox"/> 3 x 208-230 V, 60 Hz
	<input type="checkbox"/> 3 x 415 V, 50 Hz	<input type="checkbox"/> 3 x 460 V, 60 Hz	<input type="checkbox"/> 3 x 200-220 V, 60 Hz
	<input type="checkbox"/> 3 x 380 V, 50 Hz	<input type="checkbox"/> 3 x 480 V, 60 Hz	<input type="checkbox"/> 1 x 115 V, 60 Hz
	<input type="checkbox"/> 3 x 200 V, 50 Hz	<input type="checkbox"/> 3 x 380 V, 60 Hz	<input type="checkbox"/> other:
	<input type="checkbox"/> 1 x 230 V, 50 Hz	<input type="checkbox"/> 3 x 400 V, 60 Hz	

Motor	
Protective system IP55	
Insulation class (F)	
Ambient temperature (°C)	
Frequency control (Hz)	from <input type="text"/> to <input type="text"/>
Switch-on operations (per min)	
Motor connection plug HAN	<input type="checkbox"/> yes

Other